


# Supplementary Material: CrossNet: An End-to-end Reference-based Super Resolution Network using Cross-scale Warping


Haitian Zheng<sup>1</sup> Mengqi Ji<sup>3</sup> Haoqian Wang<sup>1,2</sup> Yebin Liu<sup>4</sup> Lu Fang<sup>1</sup>

No Institute Given


This supplementary material contains the visualization of the  $\times 8$  RefSR results evaluated on Stanford light field dataset (from Table 2 of the main paper) and Scene light field dataset (from Table 3 of the main paper).



**Fig. 1.** Visual comparison for  $\times 8$  RefSR on Scene light field dataset. The reference images are sampled at location  $(0,0)$ , where LR images are sampled at location  $(1,0)$ .



**Fig. 2.** Visual comparison for ×8 RefSR on Scene light field dataset. The reference images are sampled at location (0,0), where LR images are sampled at location (3,0).



**Fig. 3.** Visual comparison for  $\times 8$  RefSR on Scene light field dataset. The reference images are sampled at location  $(0,0)$ , where LR images are sampled at location  $(1,0)$ .

## References

1. Zheng, H., Ji, M., Wang12, H., Liu, Y., Fang, L.: Learning cross-scale correspondence and patch-based synthesis for reference-based super-resolution. In: BMVC. (2017)
2. Boominathan, V., Mitra, K., Veeraraghavan, A.: Improving resolution and depth-of-field of light field cameras using a hybrid imaging system. In: ICCP, IEEE (2014) 1–10
3. Dong, C., Loy, C.C., He, K., Tang, X.: Learning a deep convolutional network for image super-resolution. In: ECCV, Springer (2014) 184–199
4. Kim, J., Kwon Lee, J., Mu Lee, K.: Accurate image super-resolution using very deep convolutional networks. In: CVPR. (2016) 1646–1654
5. Lim, B., Son, S., Kim, H., Nah, S., Lee, K.M.: Enhanced deep residual networks for single image super-resolution. In: CVPRW. Volume 1. (2017) 3